




CSW868A

WiFi 802.11 b/g/n IoE Module



CSW868A

State-of-the-art Solution of IoE Applications.

Introduction of Products

Taijet Bointec CSW868A module with a built-in printed antenna is an intelligent Internet of Everything (IoE) platform which can be powered by Alljoyn with low power wireless connectivity. This completes networking platform enables customers to add full-featured Wi-Fi to a wide variety of products with minimal development effort and cost. It supports a network stack along with SSL security, enabling full-featured internet connectivity and reliable information exchange in a small, low-cost system.

The CSW868A module contains a Qualcomm® QCA4004 chipset. The QCA4004 is a single chip system on a chip (SoC) 1x1 802.11 b/g/n device optimized for low-power embedded applications with single-stream capability for both Tx and Rx. It has an integrated network processor with a large set of TCP/IP with IPv4/IPv6-based services. The CSW868A provides UART-based host and SPI slave interfaces for connecting to local system controllers.

Product Highlight


- Main Chipset Qualcomm® QCA4004
- IEEE 802.11 b/g/n compliant with 2.4GHz frequency band- Supporting HT20/HT40 bandwidth
- 1T1R- 802.11b: 1, 2, 5.5, 11Mbps; 802.11g: 6, 9, 12, 24, 36, 48,54Mbps ; 802.11n: Support PHY rate up to 150Mbps.
- UART/USB/SPI/I²C/GPIO interface- built-in printed antenna
- External antenna via IPEX connector (Optional)
- CE, FCC and RoHS compliant




Specification:

Feature	Specification
General	
Processor	Qualcomm® QCA4004
Frequency band	2.4GHz (2.412 GHz to 2.484 GHz)2.4GHz
Bandwidth	HT20 and HT40
Antenna	<ul style="list-style-type: none"> Built-in printed antenna External antenna via IPEX connector (Optional) 1T1R
Interfaces	<ul style="list-style-type: none"> UART USB SPI/SDIO GPIOs I²C I²S
WiFi	
Standard	IEEE 802.11 b/g/n
Internet Protocols	IPv4/IPv6, TCP/UDP, ARP/NDP, DHCPv4, ICMPv6
Security Protocols	WPS, WPA, WPA2, WAPI, WEP, TKIP
Power Consumption	
Operating Voltage	3.3 V ± 10%
Power Consumption	<ul style="list-style-type: none"> Transmit: 250 mA @16dBm Receive: 75 mA (typical) Power saving mode(DITM=1): 1.09mA Standby mode(Sleep): 130uA
Environment	
Operating Temperature	<ul style="list-style-type: none"> Industrial: -40°C ~ +85°C Commercial: -10°C ~ +65°C
Operating Humidity	<ul style="list-style-type: none"> Operating humidity: 20-70%
Dimension	
PCB Size	26 x 18 x 2.5 mm (height is 3.6mm when a coax cable is plugged into the u.FL connector)
Certificate	
<ul style="list-style-type: none"> CE FCC RoHS compliant 	

ME Drawing/placement



Applications



Bointec Authorized Distributer




 TAIJET BOINTEC CO LTD
 4F, #114, Zhouzi St., Neihu-Taipei 11493, Taiwan
 TEL: +886-2-2759-0081
 WWW.BOINTEC.COM

(C)TAIJET BOINTEC. All rights reserved. Taijet Bointec & the Taijet Bointec logo are the trademarks of Taijet Bointec, which may be registered in some jurisdictions. All other brands and product names are registered trademarks of their respective holders. Information supplied by Taijet Bointec is believed to be accurate and reliable. Taijet Bointec assumes no responsibility for any errors in this brochure. Taijet Bointec reserves the right, without notice, to make changed in product design or specifications.